Table 1. Main characteristics of the wastewater treatment systems in several stations at Fildes Peninsula

STATION	1	2	3	4	5	6
Type of Wastewater treatment	Biological, based on earthworms, and UV sterilization	Biological (Activated Sludge) plus UV sterilization	Biological system	Biological, filtration and UV sterilization	Mechanical system	Biological plus UV sterilization
Number of people	Maximal 150 in summer and 80 in winter	Maritime Station, max 25 in summer. Escudero, max 40 in summer.	80 in summer and, 40 in winter	Max 90 during summer.	Max 63 people.	Max 38 during summer and 25 in winter
Capacity	Up to 60 m <sup>3</sup> day <sup>-1</sup> of wastewater		Up to 26 ton day <sup>-1</sup> of wastewater	Up to 10 m <sup>3</sup> day. <sup>1</sup> of wastewater	Wastewater is discharged to septic tanks for treatment, and then stored in 200 L drums for removal from Antarctica	Up to 4 m <sup>3</sup> day <sup>-1</sup> of wastewater

## References

https://ir.canterbury.ac.nz/bitstream/handle/10092/14196/GCAS 11Project Tarasenko.pdf?sequence=1. Tarasenko S. Wastewater Treatment in Antarctica. 2009.

http://www.ats.aq/devAS/ats\_governance\_listinspections.aspx?lang=s. Report of the Antarctic Treaty Inspections undertaken by the People's Republic of China in accordance with Article VII of the Antarctic Treaty and Article 14 of the Environmental Protocol. 2016.

conaeia.mma.gob.cl/doc/ant\_61.doc. Fundación para la Transferencia Tecnológica de la Universidad de Chile. Plantas de Tratamiento de Aguas Servidas sin Generación de Lodos, Base Antártica Eduardo Frei Montalva, XII Región. 2005.